



Extour 15-1



SPECIFICATIONS :

System	: Active Bi-amp Powered Speaker 2-way With X.over Network Point at 1.900HZ, Use part Component Cone Driver 15" and 3" Compression Driver Tweeter
Frequency Response	: 42Hz - 20 kHz
Impedance/Power Louder	: 8-ohm / 350 watt to 15"; Cone Driver Woofer 8-ohm / 150 watt to 3"; Compression Driver Tweeter
Sensitivity SPL	: 127dB (Measured @1m / using Band Limited Pink Noise)
Directional Speaker Range	: 90° Vertical x 120° Horizontal
Directional Horn Range	: Vertical 90° / Horizontal 80°
Dimensions (W x H x D)	: 465 x 675 x 465 mm
Weight	: 38 kg



Specifications are subject to change without prior notice for future improvement

Copyright of intelligent electronic's © 2012



Extour 15-2



SPECIFICATIONS :

System	: Active Bi-amp Powered Speaker 2-way With X.over Network Point at 1.900HZ, Use part Component Cone Driver 15" and 3" Compression Driver Tweeter
Frequency Response	: 42Hz - 20 kHz
Impedance/Power Louder	: 8-ohm / 400 watt to 15"; Cone Driver Woofer 8-ohm / 150 watt to 3"; Compression Driver Tweeter
Sensitivity SPL	: 127dB (Measured @1m / using Band Limited Pink Noise)
Directional Speaker Range	: 90° Vertical x 120° Horizontal
Directional Horn Range	: Vertical 90° / Horizontal 80°
Dimensions (W x H x D)	: 465 x 675 x 465 mm
Weight	: 38 kg



Specifications are subject to change without prior notice for future improvement

Copyright of intelligent electronic's © 2012



Extour 15-3



SPECIFICATIONS :

System	: Active Bi-amp Powered Speaker 2-way With X.over Network Point at 1.900HZ, Use part Component Cone Driver 15" and 3" Compression Driver Tweeter
Frequency Response	: 42Hz - 20 kHz
Impedance/Power Louder	: 8-ohm / 450 watt to 15"; Cone Driver Woofer 8-ohm / 150 watt to 3"; Compression Driver Tweeter
Sensitivity SPL	: 127dB (Measured @1m / using Band Limited Pink Noise)
Directional Speaker Range	: 90° Vertical x 120° Horizontal
Directional Horn Range	: Vertical 90° / Horizontal 80°
Dimensions (W x H x D)	: 465 x 675 x 465 mm
Weight	: 38 kg



Specifications are subject to change without prior notice for future improvement