

# Professional Speaker System

**IE-215**



IE-15 and IE-215 series are the high performance and wide-bandwidth system. Extended frequency response is provided by a 15"(380mm) / two 15"(380mm) LF driver separately, teamed with a 1.4" exit compression driver mounted on a rotatable 80°X50° constant directivity HF horn.

## Specifications

|                        |                               |
|------------------------|-------------------------------|
| Model                  | IE-215                        |
| Type                   | 2-way passive speaker         |
| Frequency Response     | 55Hz~18KHz(+3dB)              |
| Component              | Low WF-15"x2 Hi Pa1.5"x1      |
| Rated Power            | 800W AES, 3200W peak          |
| Recommended amplifier  | 650-1000W into 4 ohms         |
| Sensitivity (1W/1M).   | 101dB                         |
| Maximum SPL            | 134dB                         |
| Nominal Impedance      | 4 ohms                        |
| Finish                 | Bare spots Gray finish        |
| Grill                  | Gray brush finished metal     |
| Dispersion             | 80° H ×50° V                  |
| Connector              | 2 × Neutrik NL4 SPEAKON       |
| Fitting                | 12× M8 inserts, mounting hole |
| Dimension(mm)          | 560x1066x496                  |
| Packing Dimension(HDW) | 1120×600×530mm                |
| Net Weight             | 62kg                          |